

Power Splitter 698-2700MHz 4:1

Features:

- Multiple-Band Frequency Ranges
- High Power Rating 300 Watt
- Low PIM, Low VSWR, Low Insertion loss
- High quality cavity type, High reliability
- Easy and simple installation



Specification:

Product Type	4-way Splitter
Model Number	PS4-0727-N300
Frequency Range	698 – 2700MHz
Insertion Loss	≤0.4dB
Distribution Loss	6 dB
VSWR	≤1.25
PIM (IM3)	≤-160dBc @+43dBm*2
Power Handling	300W
Impedance	50Ω
Connector Type	N-Female or DIN- Female
Applied Environment	Indoor / Outdoor
Relative Humidity	5 to 95%
Operating Temperature	-25 to +70°C
Protection class	IP65
Material	Cavity: Aluminum; Connector: Copper
Processing	Silver plated inner conductor
Dimension	246.4x61x25 mm

EMTS Telecom Services offers a comprehensive portfolio of enhanced coverage solutions for the Wireless Networks, Based on advanced technologies. **EMTS** proven, indoor and outdoor solutions solve a wide range of network challenges including interference and oscillation problems, challenging coverage holes, rapid response deployment and inadequate in-building coverage. Regardless of the technology or frequency, **EMTS** can provide customized coverage solutions that address any combination of unique and complex network needs for the Wireless Networks.

