

30dBm Band Selective SMR 850 MHz Bi Directional Amplifier

Model No: PR-85S-30W80



Features:

- **Bi Directional Amplifier (BDA) with 30dBm composite downlink output power**
- **Supports SMR 850 MHz, iDEN, APCO25, TETRA & LTE technologies**
- **Band Selective configuration supporting dual block with high out of band rejection**
- **User friendly control & plug and play installation**
- **Smart function which can be activated via the front panel, preventing UL interference, self-oscillation and also keeps optimal condition automatically**
- **Isolation detection function**
- **Low power consumption with sleeping mode (saving power)**
- **Linear power amplification to effectively suppress inter-modulation and spurious emission**
- **Smart Automatic Level Control (ALC) ensures output level stable and adjustable continuously**

Introduction

The EMTS Telecom Services Ltd. SMR850MHzBand Selective Bi Directional Amplifier (BDA) provides an affordable solution to solve the indoor signal coverage problems in LTE, APCO25, TETRA or PMR (Smart Zone) 800MHz systems due to signal fading and attenuation caused by architecture obstacles.

It's easy installation and maintenance helpsthe operator to get fast return on investment. The repeater is working as a relay between the BTS and mobiles. It picks upthe strongest signal from BTS via the Donor Antenna, linearly amplifiesthe signal and then retransmitsitvia the Indoor Signal Distribution System to the weak/blind coverage area and the mobile signal is also amplified and retransmitted to the BTS via the opposite direction. The band-selective function can choose to amplify the signal within the customized band.Hence, the installation of the Repeater is easy, simply just plug and play. The repeater status can be known during installation with indication on the repeater front panel, which is very convenient to installation teams.



EMTS Telecom Services Ltd. offers a comprehensive portfolio of enhanced coverage solutions for the Wireless Networks, Based on advanced technologies. **EMTS** proven, indoor and outdoor solutions solve a wide range of network challenges including interference and oscillation problems, challenging coverage holes, rapid response deployment and inadequate in-building coverage. Regardless of the technology or frequency, **EMTS** can provide customized coverage solutions that address any combination of unique and complex network needs for the Wireless Networks.

Technical Specifications:

1. Electrical Specification		
	Uplink	Downlink
Frequency Range	806 –824 MHz Full or any partial bandwidth	851–869 MHz Full or any partial bandwidth
Minimum Gain	≧ 80dB	
Auto Gain Control(AGC)	≧ 25dB	
Auto Gain Setup Range(Inside)	31dB/1dB step	
Gain Flatness	+/- 1.5 dB max	
Maximum Input power	0 dBm	
Output Power	24 dBm	30 dBm
Intermodulation Products	9KHz~1GHz	≧ -30 dBm
	1GHz~12.75GHz	≧ -30dBm
Spurious Emission	9KHz~1GHz	≧ -36dBm
	1GHz~12.75GHz	≧ -30dBm
Out of Band Rejection	± 400 KHz	≧ 25 dBc
	± 600 KHz	≧ 35 dBc
	± 1 MHz	≧ 45dBc
	± 5 MHz	≧ 50 dBc
Noise Figure	≧ 6dB	
VSWR	≧ 1.5	
Group Delay	≧ 5 μ s	
Power Consumption	≧ 100 W	
Power Supply	AC 220V±20%,50±5Hz	
2. Mechanical specification		
Dimensions	330 x 280 x 90 mm	
Weight	15 kg	
I/O Connector/ Impedance	N-female / (Nominal)50Ω	
3. Environmental specification		
IP Rating	IP65	
Operating Temperature	-10°C to 50°C	
4. Monitoring specification		
LED indication	Alarm LED	Antenna isolation is lower than the isolation for equipment installation Or ALC1~5dB,red
	Power LED	DC ON/OFF

About EMTS Telecom Services Ltd.:

EMTS is a leading supplier of high-quality RF coverage solutions designed to maximize wireless network coverage in difficult RF environments and complex settings. The company specializes in extending RF radio coverage to rural areas, office buildings, subways, tunnels and shadowed areas. The EMTS coverage solution supports all major mobile technologies and standards of wireless Networks.

All rights reserved - Specifications are subject to change without notice

